

Set - Circumferential belt measuring unit Silent Move WDGMEUN

For heights up to 70 metres (230 ft)



- Measuring set for easy installing the belt on existing brackets in the elevator shaft.
- Quiet and non-slip digital shaft copying for universal mounting on a lift cabin
- Use up to speeds of 4 m/s (800 ft/min).
- Particularly quiet and smooth-running, thanks to special belts and low-noise suspension.
- User-friendly, reliable alternative to switches and sensors.
- Accuracy in the shaft:
 - Incremental encoder WDG158B
up to 0.08 mm/pulse (0.0031496 inch/pulse) at 5000 pulses
 - Absolute encoder WDGA58B multiturn, with
CANopen interface: 4,096 steps/turn
and 262,144 (18 bit multiturn) turns,
CANopen LIFT interface: 4,096 steps/turn
and 262,144 (18 bit multiturn) turns or
SSI interface: 4,096 (12 bit) steps/turn and
8,192 (13 bit multiturn) turns
- Quick and easy mounting with our complete belt fixing and tensioning set.

www.wachendorff-automation.com/silent-move

The quiet **Silent Move** belt shaft copying devices are measuring units which are installed quickly and easily in the shaft.
All installation components required for standard installation to the lift cab rail or on the wall are supplied.

Noticeably quieter in a noise comparison*:

Conventional System: 92 db
Silent Move: 68 db

*measured directly at the idler pulley at 4 m/sec (800 ft/min).

Put together your own unit for shaft copying, by selecting an encoder and specifying the length of the special belt.



Incremental encoder
WDG158B



Absolute encoder
WDGA58B

Incremental encoders WDG1:

Calculation of resolution in the shaft:

Effective circumference of pulley: 401.11 mm (15.7917322835 inch)

$$\text{Res. in mm (inch)} = \frac{401.11 \text{ mm (15.7917322835 inch)}}{\text{Pulse number of encoder (PPR)}}$$

$$\text{Res. in pulses/mm (inch)} = \frac{\text{Pulse number of encoder (PPR)}}{401.11 \text{ mm (15.7917322835 inch)}}$$

Calculation of the limit frequency:

$$f_g \text{ (Hz)} = \frac{\text{Pulse number of encoder (PPR)} \times \text{max. speed (m/sec) (ft/sec)}}{0.40111 \text{ m (1.3153999 ft)}}$$

Calculation of the traverse path:

$$s \text{ (m) (ft)} = \frac{\text{Pulses (l)}}{\text{Pulse number of encoder (PPR)}} \times 0.40111 \text{ m (1.3153999 ft)}$$



Self-guiding special belt for exceptionally quiet, non-slip measuring with noise-reducing wheel.

Ordering information - Circumferential belt measuring system WDGMEUN:

Description:	Order No.:
Incremental variants Unit (without encoder): 2 guide pulleys, encoder attachment, tensioning device and fixing for the belt. Please order the special belt separately. (see below: Silent Move special belt, calculation of length)	WDGMEUN
Unit with incremental encoder WDG1 58B10600ABNH24SC8 and 15 m cable (KI 8-67-15S): For an accuracy of measurement of 0.669 mm (0.03 inch) or 1.5 pulses/mm (37.99 pulses/inch) with a limit frequency of 5.98 kHz and a cab speed of 4 m/s (787.4 ft/min). Encoder type 58B10600ABNH24SC8: Shaft: Ø 10 mm, pulse number: 600 PPR, channels AB and zero pulse, power supply 10 VDC up to 30 VDC, channels push-pull, sensor connector 8-pol. radial, 15 m cable (KI 8-67-15 S)	WDGMEUN58B10600ABNH24SC8
Unit with incremental encoder 58B101000ABNH24SC8 and 15 m cable (KI 8-67-15 S): For an accuracy of measurement of 0.4 mm (0.02 inch) or 2.5 pulses/mm (63.324 pulses/inch) with a limit frequency of 9.972 kHz and a cab speed of 4 m/s (787.4 ft/min). Encoder type 58B101000ABNH24SC8: Shaft: Ø 10 mm, pulse number: 1,000 PPR, channels AB and zero pulse, power supply 10 VDC up to 30 VDC, channels push-pull, sensor connector 8-pol. radial, 15 m cable (KI 8-67-15 S)	WDGMEUN58B101000ABNH24SC8
Unit with incremental encoder 58B2500ABNH24SC8 and 15 m cable (KI 8-67-15 S): For an accuracy of measurement of 0.16 mm (0.01 inch) or 6.23 pulses/mm (158.31 pulses/inch) with a limit frequency of 24.93 kHz and a cab speed of 4 m/s (787.4 ft/min). Encoder type 58B102500ABNH24SC8: Shaft: Ø 10 mm, pulse number: 2,500 PPR, channels AB and zero pulse, power supply 10 VDC up to 30 VDC, channels push-pull, sensor connector 8-pol. radial, 15 m cable (KI 8-67-15 S)	WDGMEUN58B102500ABNH24SC8
Find your incrementalen encoder: With the aid of the calculation forms for limit frequency and resolution in the shaft and the data sheet WDG158B. All variants defined except optional shaft sealed to IP67.	WDGMEUN58B10XXXXYYYZZSC8
Absolute variants WDGA58B CANopen, WDGA58B CANopen LIFT or WDGA58B SSI Unit with absolute multiturn encoder with CANopen CiA 406 interface: For an accuracy of measurement of 0.0979 mm (0.0038 inch) or 10.21 steps/mm (259.38 steps/inch). Binary Code: 4,096 (12 bit) steps/revolution and max. 262,144 (18 bit) revolutions. Power supply 10 VDC up to 30 VDC, 5 pin. connector, radial, 10 m bus line connector and female connector, T-junction, termination resistor.	WDGMEUN58B101218COAB00CC5
Unit with absolute multiturn encoder with CANopen LIFT CiA 417 interface: For an accuracy of measurement of 0.0979 mm (0.0038 inch) or 10.37 steps/mm (259.38 steps/inch), configurable. Binary Code: 4,096 (12 bit) steps/revolution and max. 262,144 (18 bit) revolutions, configurable. Power supply 10 VDC up to 30 VDC, 5 pin. connector, radial 10 m bus line connector and female connector, T-junction, termination resistor.	WDGMEUN58B101218CLAB00CC5
Unit with absolute multiturn encoder with synchronous serial interface SSI*: For an accuracy of measurement of 0.0979 mm (0.0038 inch) or 10.21 steps/mm (259.38 steps/inch). * Gray Code (G)/Binary Code (B): 4,096 (12 bit) steps/revolution and 8,192 (13 bit) revolutions. Power supply 10 VDC up to 30 VDC, 8 pin connector, radial, 10 m cable Comprehensive technical information on WDGA 58B CANopen / WDGA 58B CANopen LIFT / WDGA 58B SSI - www.wachendorff-automation.com/wdga58bcan / wdga58bcanlift / wdga58bssi	WDGMEUN58B101218SIAX01CC8 X = G or B
Silent Move special nubbed belt: Calculation of the length: Transport height x 2 + 10 m (extend accordingly for transition points) 20 m 35 m 50 m 60 m 80 m 200 m-drum 500 m-drum Special nubbed belt (XXX = figures in metres)	WDGMR020 WDGMR035 WDGMR050 WDGMR060 WDGMR080 WDGMR200 WDGMR500 WDGMRXXX