



Datasheet

초소형 길이측정 엔코더-LMSCA32




Wachendorff Automation ... systems and encoders

- Complete systems
- Industrial rugged encoders to suit your application
- Standard range and customer versions
- Maximum permissible loads
- 48-hour express production
- Made in Germany
- Worldwide distributor network



관련 동영상 링크

Robust length measurement system LMSCA32



- 새로운스프링암을 장착한 150m 또는 200mm측정 휠을 가진 초소형의길이측정시스템-WDGN 36A엔코더
- 최대 0.01mm/펄스
- 다양한 표면에적합
- 외부충격진동 흡수가능
- 중앙나사조정으로 그리드 세팅 각도 손쉽게조작가능
- 조립된 앵글 브라켓을 통해 손쉽게 분해가능

www.wachendorff-automation.com/lmsca32-wdgp

Resolution WDGP 36A with

Measuring systems LMSxxxKH, LMSxxxKG, LMSxxxNG:

200 ppr:	1 pulse/mm = 1.0 mm/pulse
2000 ppr:	10 pulses/mm = 0.1 mm/pulse
5000 ppr:	25 pulses/mm = 0.04 mm/pulse
16000 ppr:	80 pulses/mm = 0.0125 mm/pulse

Measuring system LMSxxxGR:

150 ppr:	1 pulse/mm = 1.0 mm/pulse
1500 ppr:	10 pulses/mm = 0.1 mm/pulse
3750 ppr:	25 pulses/mm = 0.04 mm/pulse
15000 ppr:	100 pulses/mm = 0.01 mm/pulse

Mechanical Data of the system modules

Housing encoder

Flange	synchro flange
Flange material	aluminium
Housing cap	stainless steel

Shaft(s)

Shaft material	stainless steel
Starting torque	approx. 0.2 Ncm at ambient temperature

Shaft	Ø 6 mm shaft with flat
Shaft length	L: 11.5 mm
Max. permissible shaft loading radial	80 N
Max. permissible shaft loading axial	50 N

Bearings

Max. operating speed	12000 rpm
----------------------	-----------

Spring loaded arm

Adjustable prestressing force	0 N up to 20 N in steps of 5 N
Length of spring lever axis	74.5 mm
Material	aluminum
Contact pressure	adjustable, 3°-step equates 5 N pressure increase

Machinery Directive: basic data safety integrity level

MTTF _d	1200 a
Mission time (T _M)	20 a
Nominal service life (L _{10h})	1.7 x 10 ¹⁰ revs. at 20 % rated shaft load and 12000 rpm
Diagnostic coverage (DC)	0 %

Electrical Data

Power supply/Current consumption	4.75 VDC up to 32 VDC: typ. 80 mA
Output circuit	TTL, HTL
Pulse frequency	HTL up to 16384 ppr: max. 600 kHz TTL up to 16384 ppr: max. 1 MHz
Channels	ABN and inverted signals
Load	max. 40 mA / channel
Circuit protection	inverse-polarity and short-circuit protection

Accuracy

Phase offset	90° ± max. 8.5 % of a period duration
pulse-/pause-ratio	50 % ± max. 7 %

General Data

Weight	approx. 270 g
Connection	Connector radial
Protection rating (EN 60529)	IP67, shaft sealed to IP65

Operating temperature

LMSxxxKH:	-10 °C up to +70 °C
LMSxxxKG:	-10 °C up to +70 °C
LMSxxxNG:	-10 °C up to +50 °C
LMSxxxGR:	-40 °C up to +85 °C

Range of application measuring wheel U = 200 mm



LMSxxxKH: (even) Plastic, painted surfaces, paper, paste-board, wood, metal, textiles.



LMSxxxKG: (fluted) Plastic, painted surfaces, paper, paste-board, wood, metal, textiles.



LMSxxxNG: (pimpled) Textiles.

Range of application measuring wheel U = 150 mm



LMSxxxGR: (even) Wood, metal, conveyor belts, paper, textiles.

More information


General technical data and safety incremental encoders

www.wachendorff-automation.com/gtd

Options

www.wachendorff-automation.com/acc

Sensor-connector (M12x1) SC, 8-pin



Description

SC8 radial, 8-pin, connector connected to encoder housing

Assignment	
	SC8
	8-pin
Steckerbild	
GND	1
+UB	2
A	3
B	4
N	5
SET	-
A inv.	6
B inv.	7
N inv.	8
n. c.	-
Shield	-



LMSCA321000024KH
 LMSCA321000005KH
 LMSCA321000024KG
 LMSCA321000005KG
LMSCA320100024NG
 LMSCA320100005NG
 LMSCA320100024KH
 LMSCA320100005KH
 LMSCA320100024KG
 LMSCA320100005KG
LMSCA320040024NG
 LMSCA320040005NG
 LMSCA320040024KH
 LMSCA320040005KH
 LMSCA320040024KG
 LMSCA320040005KG
LMSCA320012524KH
 LMSCA320012505KH
 LMSCA320012524KG
 LMSCA320012505KG
LMSCA320012505NG

* Range of application measuring wheel U = 200 mm

1 LMSxxxKH	Plastic, painted surfaces, paper, pasteboard, wood, metal, textiles.
2 LMSxxxKG	Plastic, painted surfaces, paper, pasteboard, wood, metal, textiles.
3 LMSxxxNG	Textiles.

Range of LMSxxxGR application measuring wheel U = 150 mm
Wood, metal, conveyor belts, paper, textiles.

LMSCA32 Errors and modifications reserved. © Wachendorff Automation GmbH & Co. KG 2022-03-24 -4-



For further information please contact our local distributor.
Here you find a list of our distributors worldwide.
http://www.wachendorff-automation.com/distributors_worldwide.html

CREKEN
(주)크레켄

경기도 성남시 중원구 사기막골로 124

SKn테크노파크 메가동 514호 우편번호:13207

Phone: 031) 608-3200 Fax: 031) 776-2320
E-Mail: sales@creken.co.kr
www.creken.co.kr

 **WACHENDORFF**

Wachendorff Automation GmbH & Co. KG
Industriestrasse 7 • D-65366 Geisenheim

Tel.: +49 (0) 67 22 / 99 65 - 25
Fax: +49 (0) 67 22 / 99 65 - 70
E-Mail: wdg@wachendorff.de
www.wachendorff-automation.com

