



M8 B-coding Straight Connector, Panel Mount, Solder, Front fastened

Male



Female



Specifications

Contacts	5
Certification	UL94V-0 CYJV(CYJV7).E321413
Pin layout(Male)	
Pin layout(Female)	
Standard	IEC 61076-2-104
Ambient temperature	-15°C~+85°C (flexible installation), -30°C~+85°C (fixed installation)
Customized temperature	-25°C ~ +85°C (flexible installation), -40°C ~ +85°C (fixed installation)
Connector insert	TPU
Connector contacts	Brass with gold plated
Coupling nut/screw	Brass with nickel plated
Seal/O-ring	Epoxy resin / FKM
Insulation resistance	≥100MΩ
Contact resistance	≤5mΩ
Earth tag/pin	Unavailable
IP rating	IP67 in locked condition
Mating endurance	>500 cycles
Rated current	3 A
Rated voltage	30V AC / DC
Wire gauge	0.25mm² (AWG24)
Panel cut-out	Refer to page 101

Part Number

Pins	wire length	Male	Female
5	0.1m	MB08MSBFF05ST-2501	MB08FSBFF05ST-2501
	0.3m	MB08MSBFF05ST-2503	MB08FSBFF05ST-2503

Default wire colors

Pin No.	
Pin 1	
Pin 2	
Pin 3	
Pin 4	
Pin 5	