




제어함 설치

-  -40 - 80 °C
-  PA 6.6
-  V0
-  IP 54



파트 번호	주문 번호	색상	적용 가능한 구멍 크기 (소형/대형)	호환되는 제품	Amm	Bmm
KD/SG -24/4	171034	Grey	4 / -	-	120	43

파트 번호	주문 번호	색상	호환되는 제품	Amm	Bmm	Cmm	Imm	Fmm	Gmm	Imm	Kmm
H24B-AG	09300240301	Grey	KD/SG -24/4	140	44	103	155	55	27	32	4.5



참고: KDT/Z 실링 링의 호환 정보는, 9.1.02를 참조해주세요

-  -40 - 80 °C
-  TPR
-  HB
-  IP 54



소형 - 실링 고무 링

파트 번호	주문 번호	색상	통과 가능 케이블(mm)	적용 가능한 구멍 크기 (소형/대형)
KDT/Z 03	171212	Black	3 - 4	● / -
KDT/Z 04	171214	Black	4 - 5	● / -
KDT/Z 05	171216	Black	5 - 6	● / -
KDT/Z 06	171218	Black	6 - 7	● / -
KDT/Z 07	171220	Black	7 - 8	● / -
KDT/Z 08	171222	Black	8 - 9	● / -
KDT/Z 09	171224	Black	9 - 10	● / -
KDT/Z 10	171226	Black	10 - 11	● / -
KDT/Z 11	171228	Black	11 - 12	● / -
KDT/Z 12	171230	Black	12 - 13	● / -
KDT/Z 13	171232	Black	13 - 14	● / -
KDT/Z 14	171234	Black	14 - 15	● / -
KDT/Z 15	171236	Black	15 - 16	● / -

실링 플러그

파트 번호	주문 번호	색상	통과 가능 케이블(mm)	적용 가능한 구멍 크기 (소형/대형)	
BTK- 	171210	Black	-	● / -	10

09

케이블 고정 플레이트