


M8 Female Molded Cable, Straight, Shielded

- Connector series: M8
- Gender: Female
- Coding: A,B
- Locking type: Fix screw
- Mounting type: Straight
- Part No.: MA08FS*F**STXXXXXX

* refers to coding type
** refers to pins number
X refers to cable specification




General information

Standard:	IEC 61076-2-104
Ambient temperature:	-40℃ ~ +80℃(fixed installation) -20℃ ~ +80℃(flexible installation)
Connector insert:	TPU; PA
Connector contacts:	Brass with gold plated
Connector overmold:	TPU
Connector nut/screw:	Brass with nickel plated
Seal / O-ring:	FKM

Insulation resistance:	≥ 100MΩ
Contact resistance:	≤ 5mΩ
Shielding:	Available
IP rating:	IP67 in locked condition
Mating endurance:	>500 cycles

Electrical data & Mechanical data

Contacts		Rated current	Voltage		Wire gauge / size		Cable jacket	Part No.
			A/C	D/C	AWG	mm ²		
03 pins	 (A-coding)	3A	50V	60V	24AWG	0.25	PVC	MA08FSAF03STXXCB25
							PUR	MA08FSAF03STXXRB25
04 pins	 (A-coding)	3A	50V	60V	24AWG	0.25	PVC	MA08FSAF04STXXCB25
							PUR	MA08FSAF04STXXRB25
05 pins	 (B-coding)	3A	30V	30V	24AWG	0.25	PVC	MA08FSBF05STXXCB25
							PUR	MA08FSBF05STXXRB25
06 pins	 (A-coding)	1.5A	30V	30V	26AWG	0.14	PVC	MA08FSAF06STXXCB14
							PUR	MA08FSAF06STXXRB14
08 pins	 (A-coding)	1.5A	30V	30V	26AWG	0.14	PVC	MA08FSAF08STXXCB14
							PUR	MA08FSAF08STXXRB14

Note: X refers to cable length

Remarks

- Please refer to Page 578 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm².
- Please refer to Page 22 for products' part number encoding rule.